

HELI合力

CBD20-410

电动托盘搬运车 Electric pallet truck

产品性能特点:

货叉进出双面托盘设计;
机械转向,舒适、经济、更可靠;
交流驱动,低噪、静音,无碳刷、免维护;
电起升,快速、高效,标配起升限位装置;
低能耗,更环保;
交流控制器,无级调速,动力强劲,多重自动保护。
锂电池采用磷酸铁锂电池,充电快,效率高。

Characteristics:

Fork fit for double-deck pallet.
Mechanical steering, comfortable, economic, more reliable.
AC driving system, low noise, quiet, without carbon brush and free maintenance.
Electric lifting, rapid, efficient, electricity limit switch is STD.
Save energy, more environmentally friendly.
AC controller, stepless, strong power, multiple automatic protection.
The LFP model lithium batteries are fast charging and efficient.





AC 电限位

货叉适用 双面托盘

CBD20-410

制造商和技术参数 Manufacturer's Data and Design Characteristics

特性	Feature	单位	
1.1 型号	Model		CBD20
1.2 配置号	Configuration No.		410
1.3 额定载重	Load capacity	kg	2000
1.4 载荷中心距	Load center	mm	600
1.5 轴距	Wheel base	mm	1407
1.6 操作类型	Operating type		乘驾式 Stand on
车轮			
Wheels			
2.1 轮子类型(前/后)	Wheels type		PU
2.2 驱动轮/平衡轮/承重轮数量	Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/4
2.3 驱动轮尺寸	Driving wheel size	mm	Φ248×75
2.4 平衡轮尺寸	Balance wheel size	mm	Φ115×55
2.5 承重轮尺寸	Bearing wheel size	mm	Φ84×80
尺寸			
Dimension			
3.1 货叉最低离地高度	Min.fork lowered height	mm	85
3.2 货叉最大起升高度	Max.fork lifting height	mm	195
3.3 最大起升行程	Max.lifting height	mm	110
3.4 货叉外侧间距	Outside width between forks	mm	550/600/650/685
3.5 货叉内侧间距	Inside width between forks	mm	210/260/310/345
3.6 货叉长度	Fork length	mm	1150/1200
3.7 货叉宽度	Fork width	mm	170
3.8 货叉厚度	Fork thickness	mm	75
3.9 整车全长,踏板收起/放下	Overall length	mm	1874/2247
3.10 车体宽度	Overall width	mm	725
3.11 整车高度(含手柄)	Overall height(With handle)	mm	1475
3.12 整车高度(不含手柄)	Overall height(Without handle)	mm	940
3.13 最小转弯半径,踏板收起/放下	Min.Turning radius	mm	1680/2060
3.14 最小通道宽度(满载800×1200托盘放置)	Min.Aisle width for pallets 800×1200	mm	2000/2320
3.15 最小通道宽度(满载1000×1200托盘放置)	Min.Aisle width for pallets 1000×1200	mm	2030/2340
性能			
Performance			
4.1 最大行驶速度,满载/空载	Travel speed,laden/unladen	km/h	5.5/6
4.2 最大起升速度,满载/空载	Lift speed,laden/unladen	mm/s	30/35
4.3 最大下降速度,满载/空载	Lowering speed,laden/unladen	mm/s	40/35
4.4 爬坡能力,满载/空载	Gradeability,laden/unladen	%	6/16
电气配置			
Electrical configuration			
5.1 驱动电机/起升电机	Drive motor/ Lift motor	KW	AC1.5/DC1.2
5.2 制动	Brake	V/Ah	电磁/再生 Electromagnetic/Regenerative
电池			
Battery			
5.4 电池电压/容量	Battery voltage/capacity		铅酸电池Lead-acid battery 24/210 锂电池Lithium battery (optional) 24/200
控制器	Controllor		ZAPI ZAPI
6.1 电池重量	Battery	kg	192 96
6.2 自重(包含电池)	Service weight (with battery)	kg	664 544



安徽合力股份有限公司
ANHUI HELI CO., LTD.
地址 / 中国 合肥方兴大道668号
Add / No.668, FangXing Road, Hefei, China
邮编 (Post Code) / 230000

客服热线 (Customer Service Hotline) / 4001-600761
服务电话 (Service Tel) / +86-551-63689000, 63648005

* 本公司保留更改产品设计和规格的权利,恕不另行通知。
* Our products are subject to improvements and changes without notice.

设计/制图: 李可立/陈勇_20200807